

5G Block

5G12155 12V 155AH

Series	FS	Warranty	1 Year
Volts	12	BCI	GC12
Cells	6	Plates/Cell	11
Terminal Type	UTL		
Included Hardware	Stainless Steel K-Lock Nut		
Size & Thread	5/16"-18		

Charge

Charge Voltage Range	14.7-15 V/cell @ 25°C (77°F)
Recommended Charge Current Capacity (String)	15 A
Maximum Charge Current (String)	25 A
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

Capacity

Cold Crank Amps (CCA) 0°F / -18°C	563
Marine Crank Amps (MCA) 32°F / 0°C	703
Reserve Capacity (RC @ 25A)	284 Minutes
Reserve Capacity (RC @ 75A)	79 Minutes

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	206 AH	2.06 A
@ 72 Hour Rate	195 AH	2.71 A
@ 50 Hour Rate	184 AH	3.69 A
@ 20 Hour Rate	155 AH	7.75 A
@ 15 Hour Rate	147 AH	9.82 A
@ 10 Hour Rate	136 AH	13.64 A
@ 8 Hour Rate	133 AH	16.66 A
@ 5 Hour Rate	122 AH	24.49 A
@ 1 Hour Rate	62 AH	62 A

Amphere hour capacity ratings based on specific gravity of 1.280 at 25°C (77°F). Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

Specifications




SAI GLOBAL
ISO 9001
Quality

Weight	38.0 kg	82.5 lbs
Length	35.3 cm	13.13"
Width	18.1 cm	7.17"
Height Inc. Term.	27.4 cm	10.8"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Electrolyte Reserve	38 mm	1.5"
Container	Polypropylene	
Cover	Polypropylene	
Handles	Top Molded Strap Brackets	

Cycle Life vs. Depth of Discharge



Voltage vs. Depth of Discharge

